

# T1 Tee

## -Standard Radius-




Tees are made of ductile iron per ASTM A536 Gr. 65-45-12 C-E dimensions are manufacturer's standard.  
Standard fitting pressure ratings conform to the ratings of coupling.

Industrias Especializadas Oliva  
<https://ieso.com.mx/tienda/>  
 (686) 568-9002

Pressure rating 300PSI / 2.07MPa

UL Listed & FM Approved



Model E2 Tee (Standard Radius)			
Nominal Size mm/in	Pipe O.D mm/in	C E mm/in	weight kg/Lbs
25	33.7	58	0.4
1	1.315	2.275	0.9
32	42.4	70	0.7
1.25	1.660	2.756	1.5
40	48.3	70	0.9
1.5	1.9	2.756	2.0
50	60.3	83	1.3
2	2.375	3.255	2.9
65	73	95	2.2
2.5	2.875	3.745	4.8
76.1	76.1	95	2.3
3OD	3	3.745	5.1
80	88.9	108	3.1
3	3.5	4.25	6.8
100	114.3	127	4.5
4	4.5	5	9.9
139.7	139.7	140	6.5
5	5.5	5.5	14.3
125	141.3	140	6.5
5	5.563	5.5	14.3
165.1	165.1	165	9.4
6-1/2OD	6.5	6	20.8
150	168.3	165	10.0
6	6.625	6	22.0
200	219.1	197	20.0
8	8.625	7.755	44.0
250	273	229	31.0
10	10.75	9	68.2
300	323.9	254	43.9
12	12.750	10	96.7