

E2 45° Elbow

- Standard Radius -


Elbows are made of ductile iron per ASTM A536 Gr. 65-45-12 and or ASTM A395 Gr. 65-45-15. C-E dimensions are manufacturer's standard.



Industrias Especializadas Oliva
<https://ieso.com.mx/tienda/>
 (686) 568-9383

Pressure rating 300PSI / 2.07MPa

UL Listed & FM Approved



Model E2 45° Elbow (Standard Radius)

Nominal Size mm/in	Pipe O.D mm/in	C E mm/in	weight kg/Lbs
1	1.315	1.75	0.5
25	33.7	45	0.2
1¼	1.660	1.75	0.7
32	42.4	45	0.3
1½	1.9	1.75	0.9
40	48.3	45	0.4
2	2.375	2	1.5
50	60.3	51	0.7
2½	2.875	2.25	2.1
65	73	57	0.9
3OD	3	2.25	2.1
76.1	76.1	57	0.9
3	3.5	2.5	2.9
80	88.9	64	1.3
4	4.5	3	4.4
100	114.3	76	2
5	5.5	3.25	6.4
139.7	139.7	83	2.9
5	5.563	3.25	6.6
125	141.3	83	3
6-1/2OD	6.5	3.5	8.9
165.1	165.1	89	4
6	6.625	3.5	8.9
150	168.3	89	4
8	8.625	4.25	19
200	219.1	108	8.6
10	10.750	4.75	34.2
250	273	121	15.5
12	12.750	5.25	49.5
300	323.9	133	22.5